CAVALRY EZ

DRODUCT NAME

ITIFICATION		

CAVALRYEZ
SABRE INITIATIVES LLC.
2508 Trott Ave SW
Wilmar, MN 56201
320-235-8518
EC PHONE: US & Canada: 1-800-424-9300

Category 4

Category 1 Category 1

Category 1B

CHEMICAL NAME: Proprietary mixture CHEMICAL FAMILY: CHEMICAL FORMULA: Mixture

PRODUCT USE: Agricultural adjuvant

SECTION 1 NOTES: None

### SECTION 2: HAZARDS IDENTIFICATION

### GHS Ratings:

### Toxicity Categories

Acute toxicity (Oral) Skin corrosion/ irritation Eye damage/ irritation Corrosive to metal

!



### **GHS HAZARDS**

H290 May be corrosive to metals. H302 Harmful if swallowed. H314 Causes severe skin burns and eye damage. H318 Causes serious eye damage.

### GHS PRECAUTIONS

P102 Keep out of reach of children.

P103 Read label before use.

P233 Keep container tightly closed.

P234 Keep only in original container.

P260 Do not breathe vapors or spray.

P264 Wash hands thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.

P280 Wear protective gloves, protective clothing, eye protection and face protection. P301+310+330 IF SWALLOWED: Immediately call poison center, doctor or physician.

Rinse Mouth.

P302+361+338 IF ON SKIN: (or hair): Remove or take off immediately all contaminated clothing. Rinse skin with water or shower.

P304+340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

P305+351+338 IF IN EYES: Rinse cautiously with water for several minutes.

Remove contact lenses if present and easy to do then continue rinsing cautiously. P310 Immediately call a POISON CENTER, doctor or physician.

P361 Remove or take off immediately all contaminated clothing.

P363 Wash contaminated clothing before reuse.

P390 Absorb spillage to prevent material damage.

P402 Store in a dry place.

P403+235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

P406 Store in corrosive resistant HDPE, stainless steel or polypropylene containers with a resistant inner liner

P501 Dispose of contents/container to an approved waste disposal facility in accordance with all federal, state and local regulation

CAVALRY EZ

a trade

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS						
INGREDIENT Urea, sulfuric acid 1:1 Trade Secret	<u>CAS NO.</u> 57-13-6, 7664-93-9 Trade Secret	<u>% WT</u> 20 - 30% 5 - 10%				
NOTE: Product does NOT contain any	pesticides or pest control agents.					
SECTION 3 NOTES: These specific cl secret.	nemical identities and or exact percentage (cond	centration) of composition have been withheld as				

CARCINOGENIC OSHA:	No	ACGIH:	No	NTP:	No	IARC:	No	OTHER: No	
SECTION 4. EID									

Have the product container with you when calling a poison control center or doctor, or going for treatment.

**IF IN EYES:** Immediately call a poison center, doctor or physician. Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do then continue rinsing.

IF ON SKIN OR CLOTHING: Remove or take off immediately all contaminated clothing. Rinse skin with water or shower. Call a poison center or physician to specify the appropriate source of emergency medical advice.

**IF SWALLOWED:** Immediately call a poison center or physician to specify the appropriate source of emergency medical advice. Unless advised otherwise by a poison control center or doctor, have person rinse mouth with water, if able. Do not give anything by mouth to an unconscious person.

**IF INHALED:** If breathing is difficult, remove person to fresh air and keep at rest in a position comfortable for breathing. If person is not breathing, call 911 or an ambulance, and then give artificial respiration, preferably mouth to mouth if possible.

### NOTES TO PHYSICIANS OR FIRST AID PROVIDERS:

#### SECTION 4 NOTES: None

SECTION 5: FIRE FIGHTING MEASURES							
NFPA HAZARD CLASSIFICATION HEALTH: 2 FLAMMABILITY:	1 <b>REACTIVITY:</b> 0 <b>OTHER</b> : -						
IN CASE OF FIRE:	Water, carbon dioxide, dry chemical or foam.						
SPECIAL FIRE FIGHTING PROCEDURES:	Use full turn-out gear and self-contained breathing apparatus. Dike and collect water using media appropriate for acidic water.						
UNUSUAL FIRE AND EXPLOSION HAZARDS: None known							
HAZARDOUS DECOMPOSITION PRODUCTS: Under fire conditions, oxides of carbon, sulfur and nitrogen.							
SECTION 5 NOTES: None							
SECTION 6: ACCIDENTAL RELEASE MEASURES							

ACCIDENTAL RELEASE MEASURES: Absorb spillage to prevent material damage. Surround and absorb all spills. Material should be collected and disposed in proper manner. Dike the area to prevent spill from spreading. Soak up spill with a suitable absorbent such as clay, sawdust or kitty litter. Sweep up absorbed material and place in a chemical waste container for disposal. Wear suitable protective equipment.

SECTION 6 NOTES:

None

CAVALRY EZ

SECTION 7: HANDLING AND STORAGE

HANDLING	Keep out of reach of children. Read label before use. May rupture unvented containers. Store in ventilated containers only. Do not eat, drink or smoke when using this product .Do not breathe vapors or spray. Wash hands thoroughly after handling. Wear protective gloves, protective clothing, eye protection and face protection. Wash contaminated clothing before reuse.
STORAGE:	Store locked up. Will corrode incompatible materials. Extremely corrosive to copper, aluminum, zinc and mild steel. Polyethylene or polypropylene or other polymers are acceptable materials of construction. Store in a ventilated container only. Storage tanks should be vented and painted white or in light heat deflecting colors. Ensure that all pumps, valves, meters gaskets, etc are of compatible material. Store in a dry place. Store in a cool well ventilated area. Keep in original container tightly closed. Do not reuse empty container. Do not store with food, feed, or other material to be used or consumed by humans or animals. Do not contaminate water supplies. <b>STORE BETWEEN 40° AND 90° F.</b>
SECTION 7 NOTES:	None

### SECTION 7 NOTES:

### SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Contains no substances with occupational exposure limit values HMIS=C

•	•					
VENTILATION:	Local exhaust ventilation recommended if generating vapor, dust, or mist. If exhaust ventilation is not available or inadequate, use OSHA or NIOSH approved respirator as appropriate.					
RESPIRATORY PROTECTION:	Not necessary unless ventilation is inadequate. Then use OSHA or NIOSH approved respirator, as appropriate.					
EYE PROTECTION:	Chemical goggles					
SKIN PROTECTION:	Acid impermeable gloves, long-sleeved shirts and pants, apron.					
OTHER PROTECTIVE CLOTHING OR EQUIPMENT: Eye wash and safety shower should be easily accessible. Dust mask for odor optional.						
WORK HYGIENIC PRACTICES: Wash thoroughly with soap and water after handling product and before eating, drinking, or using tobacco products. Clean affected clothing, shoes, and protective equipment before reuse.						
EXPOSURE GUIDELINES:	If exposed, see section 4 for acute	exposure first aid.				
SECTION 8 NOTES:	None					
SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES						
APPEARANCE: PHYSICAL STATE:	Clear viscous Liquid	VAPOR DENSITY (AIR = 1):	Unknown			

APPEARANCE: PHYSICAL STATE: ODOR: ODOR THRESHOLD;	Clear viscous Liquid None Not known	VAPOR DENSITY (AIR = 1):	Unknown F: Unknown C: Unknown
pH AS SUPPLIED: pH (Other):	<1 1 – 2 at 2%	RELATIVE DENSITY:	9.538 lb/gal to 9.738 lb/gal
INITIAL BOILING POINT:	F: Unknown C: Unknown	SPECIFIC GRAVITY	1.145 to 1.169
BOILING POINT RANGE:	F: Unknown C: Unknown	SOLUBILITY IN WATER:	Soluble
MELTING POINT:	F: Unknown C: Unknown	PARTITION COEFFICIENT: (n-octano	l/water): Unknown
FLASH POINT:	<b>F</b> : >200 <b>C</b> : >93	AUTO-IGNITION TEMPERATURE:	Unknown
METHOD USED: FLAMMABILITY (solid, gas):	PMCC Can burn	DECOMPOSITION TEMPERATURE:	Unknown
FLAMMABLE LIMITS IN AIR, UP		VISCOSITY: @	Not determined F: Unknown C: Unknown

### SECTION 9 NOTES: VALUES ARE NOT PRODUCT SPECIFICATIONS.

Note: These physical data are typical values based on material tested but may vary from sample to sample. Typical values should not be construed as a guaranteed analysis of any specific lot or as specification items.

CAVALRY EZ

SECTION 10: STABILITY AND REAC	TIVITY				
STABILITY: Stable	Unstable	0			
CONDITIONS TO AVOID (STABILITY		This material may vigorously decompose releasing carbon dioxide gas if heated above 230-300°F.			
INCOMPATIBILITY (MATERIAL TO A		Avoid contact with oxidizers. May be extremely hazardous in contact with chlorates. This material is corrosive to metal. Avoid contact with nitrates, hypochlorites (e.g., chlorine bleach), sulfides, or cyanides which will generate toxic gases. Contact with alkaline materials (e.g., aqua ammonia and caustics) will generate heat.			
HAZARDOUS DECOMPOSITION OR BY-PRODUCTS: Under fire conditions, oxides of carbon, nitrogen and sulfur. Small amounts of carbon dioxide will be released under normal conditions. Vented caps should be used on all containers and vessels.					
HAZARDOUS POLYMERIZATION:		Will not occur			
CONDITIONS TO AVOID (POLYMER	IZATION): N	lone known			
SECTION 10 NOTES:		None			
SECTION 11: TOXICOLOGICAL INFO	ORMATION				
TOXICOLOGICAL INFORMATION:	Not availa	ble			
MIXTURE TOXICITY	Not availa	ble			
COMPONENT TOXICITY	Not availa	ble			
SECTION 11 NOTES:	None				
SECTION 12: ECOLOGICAL INFORM	IATION				
ECOLOGICAL INFORMATION:	Not availa	ble			
ECOTOXICITY:	Not availa	ble			
BIOACCUMULATIVE POTENTIAL: N	ot available				
MOBILITY IN SOIL:	Not availa	ble			
OTHER ADVERSE EFFECTS:	Not availa	ble			
SECTION 12 NOTES:	None				
SECTION 13: DISPOSAL CONSIDER	ATIONS				
WASTE DISPOSAL METHOD:		ntaminate water, food or feed by storage or disposal. Dispose of contents in container to an waste disposal facility in accordance with all federal, state and local regulations.			
CONTAINER DISPOSAL:		e (or equivalent) adding rinse water to application tank. Offer container for recycling or in a sanitary landfill or by other procedures approved by local regulations.			
RCRA HAZARD CLASS:	None				
SECTION 13 NOTES:	None				

### **U.S. DEPARTMENT OF TRANSPORTATION**

Proper shipping name: Corrosive Liquid, Acidic, Organic N.O.S. (contains monocarbamide dihydrogen sulfate)

DOT Shipping Description: Identification Number:	Corrosive Liquid, Acidic, Organic N.O.S. (contains monocarbamide dihydrogen sulfate) UN3265
Proper Shipping Name:	Corrosive Liquid, Acidic, Organic N.O.S. (contains monocarbamide dihydrogen sulfate)
Hazard Class: Packing Group:	8 II
Label Required:	CORROSIVE
If shipping limited quantity:	49 CFR 173.15(b)(1) inner container not over 1.0 L (0.3 gallons)

**U.S. Surface Freight Classification:** ADHESIVES, ADJUVANTS, SPREADERS OR STICKERS (NMFC 4610; CLASS: 60) Consult appropriate ICAO/IATA and IMDG regulations for shipment requirements in the Air and Maritime shipping modes.

OTHER AGENCIES:	None
SECTION 14 NOTES:	None

### SECTION 15: REGULATORY INFORMATION

#### U.S. FEDERAL REGULATIONS

TSCA (TOXIC SUBSTANCE CONTROL ACT): Mixture not I

Mixture not listed or excluded from listing.

CERCLA (COMPREHENSIVE RESPONSE COMPENSATION, AND LIABILITY ACT): Not Regulated

SARA TITLE III (SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT): Not Regulated

**311/312 HAZARD CATEGORIES:** This product has been reviewed according to the EPA "Hazard Categories" promulgated under Section 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

Immediate Health Hazard

#### 313 REPORTABLE INGREDIENTS:

This product contains no substances subject to the reporting requirements of Section 313 of the Superfund Amendments and Reauthorization Act of 1986 (SARA Title III) or 40 CFR Part 372 in concentrations above the de minimis concentration level.

Section 302/304 Extremely Hazardous Substances				
Chemical Name	CAS Number	Range in %	TPQ	RQ
Residual ethylene oxide (typical)	75-21-8	< 0.001	Below r	eportable concentrations

WARNING! This product contains a detectable amount of ethylene oxide, which is known to the State of California to cause cancer and/or reproductive toxicity.

Ethoxylated products may contain residual amounts of ethylene oxide (EO) which can accumulate in the container headspace and be released into the ambient environment. This process is enhanced when the product is agitated, as during tank car loading and unloading, and blending operations. Ethylene oxide causes tumors in laboratory animals. The Occupational Safety and Health Administration (OSHA) Permissible Exposure Level (PEL) for EO is 1 ppm for an eight-hour time weighted average exposure. The standard regulates occupational exposure to EO from all sources, including products containing residual EO. It is the responsibility of the employer to comply with OSHA ethylene oxide standard (29) CFR 1910.1047).

INTERNATIONAL REGULATIONS: None

SECTION 15 NOTES: None

### **SECTION 16: OTHER INFORMATION**

### OTHER INFORMATION: None

#### DISCLAIMER:

The recommendation for safe handling and protection procedures is believed to be generally suitable for the standard uses of this compound. However, each user should identify his intended uses of this material and determine whether they are appropriate. All data included in this document is released as typical values and should not be utilized to determine the suitability of this material for a particular use or purpose.

CAVALRY EZ No warranty, either expressed or implied, is hereby made, nor do we give permission, inducement, or recommendations to practice any patented invention without a license. All data is offered for consideration, investigation and verification purposes only.